



LABOR RELATIONS DIVISION

401 Broadway NE
 Albuquerque, NM 87102
 Phone: 505-841-4400
 Fax: 505-841-4424

226 South Alameda Blvd
 Las Cruces, NM 88005
 Phone: 575-524-6195
 Fax: 575-524-6194

WWW.DWS.STATE.NM.US

Wage Decision Approval Summary

1) Project Title: building addition for Pleasant Hill Fire Dept 2025-0287
 Requested Date: 08/06/2024
 Approved Date: 08/07/2024
 Approved Wage Decision Number: CU-24-2527-B

Wage Decision Expiration Date: 12/05/2024

2) Physical Location of Jobsite for Project:
 Job Site Address: 304 NM-77
 Job Site City: Texico
 Job Site County: Curry

3) Contracting Agency Name (Department or Bureau): Curry County
 Contracting Agency Contact's Name: Carol Pipes
 Contracting Agency Contact's Phone: (575) 763-6016 Ext. 130

4) Estimated Contract Award Date: 08/06/2024

5) Estimated total project cost: \$195,800.99
 a. Are any federal funds involved?: No
 b. Does this project involve a building?: Yes - Pleasant Hill Fire Dept
 c. Is this part of a larger plan for construction on or appurtenant to the property that is subject to this project?: No
 d. Are there any other Public Works Wage Decisions related to this project?: No
 e. What is the ultimate purpose or functional use of the construction once it is completed?: to provide a building addition to the fire department

6) Classifications of Construction:

Classification Type and Cost Total	Description
General Building (B) Cost: \$195,800.99	Minor site demolition, slab on grade, plain, remove, excludes hauling Slab on grade removal, plain Selective demolition, rubbish handling, dumpster, 40 C.Y., 10 ton capacity, weekly rental, includes one dump per week, cost to be added to demolition cost 40 C.Y. capacity (10 tons) Aggregate, crushed bank gravel, loaded at the pit, prices per ton, includes material only Sand & stone, loaded at pit, crushed bank gravel Structural concrete, in place, spread footing (3000 psi), over 5 C.Y., includes forms(4 uses), Grade 60 rebar, concrete (Portland cement Type I), placing and finishing Over 5 C.Y. Reinforcing steel, in place, dowels, deformed, 2' long, #4, A615, grade 60 #4 C.I.P. concrete forms, slab on grade, slab block outs, wood, to 12" high, 1 use, includes erecting, bracing, stripping and cleaning For slab block outs, to 12" high, 1 use

	<p>Grout, door frames, 3' x 7' opening, 2.5 C.F. per opening Door frames, 3' x 7' opening, 2.5 C.F. per opening</p> <p>Welding structural steel in field, cost per welder, 2# per ton, 1/8" dia, type 6011, incl 1 operating engineer With one operating engineer per welder, 2# E6011 per ton</p> <p>Gypsum wallboard, on walls, standard, w/compound skim coat (level 5 finish), 1/2" thick With compound skim coat (level 5 finish)</p> <p>Pre-engineered steel building accessory items, insulation, un-faced, rated .6 lb density, 4" thick, R-13 Insulation, rated .6 lb. density, unfaced 4" thick, R13</p> <p>Drain, trench, polyester polymer for cement concrete encasement, 4" internal width, with heavy duty iron grate, not including trenching or concrete Heavy duty iron grate</p>
--	---